Divisio	n of Health Care Faci	lities	454	7/14/14		05/30/2014 APPROVED
STATEMENT OF DEFICIENCIES (X1) PROVIDER/SUPPLIER/CLIA AND PLAN OF CORRECTION IDENTIFICATION NUMBER;		(X2) MULTIPLE CONSTRUCTION A. BUILDING: 01 - MAIN BUIDING		(X3) DATE SURVEY COMPLETED		
NAME OF PROVIDER OR SUPPLIER STREET ADD			B. WING	05		7/2014
			DRESS, CITY, ST.	ATE, 2IP CODE		
	AMARITAN SOCIETY	CROSSVI	ARITAN WAY ILLE, TN 3855	8		
(X4) ID PREFIX TAG	SUMMARY STATEMENT OF DEFICIENCIES (EACH DEFICIENCY MUST BE PRECEDED BY FULL REGULATORY OR LSC IDENTIFYING INFORMATION)		ID PREFIX TAG	PROVIDER'S PLAN OF CORRECT (EACH CORRECTIVE ACTION SHOU CROSS-REFERENCED TO THE APPRO DEFICIENCY)	HOULD BE CONSISTS	
N 843	343 1200-8-608 (13) Building Standards		N 843		*	-
	(13) Electrical drawings shall include where applicable:			N 843 – Building Standards		
	 (a) A seal, certifying that all electrical work and equipment is in compliance with all applicable codes and that all materials are currently listed by recognized testing laboratories; (b) All electrical wiring, outlets, riser diagrams, switches, special electrical connections, electrical service entrance with service switches, service feeders and characteristics of the light and power current, and transformers when located within the building; 			l. The multi-plug adaptor was removed and replaced with an approved ground fault power strip and plug on hair dryer was replaced with the ground on 5/27/14.		
				2. All residents have the poten to be affected by this deficient practice. Maintenance departminspected skilled units for all ground fault outlets and wet are	ent	
	(c) An electrical syst applicable codes;	em that complies with		No other adaptors were found at r		
	(d) Color coding to show all items on emergency power;			3. Beauty shop employees wer educated on use of approved	e	
-	(f) Ground-Fault Circ are required in all we laundries, janitor close	that are properly labeled; and suit Interrupters (GFCI) that et areas, such as kitchens, sets, bath and tollet rooms, and feet of any lavatory.		adapters and inspection of appliance plugs before use on \$/27/14, and instructed to notifi maintenance department if adaptis needed. Use of adaptors will included in monthly preventation maintenance and will be added TELS for monitoring.	be	
	facility failed to comp	n, it was determined the ly with applicable codes.		4. Maintenance Department will complete a safety audit on the beauty shop monthly x3 and the quarterly to include use of adap Audits will be reported to the quality committee for recommendations.	en	
	olth Core Englisher			•	f	

Division of Health Care Facilities

LABORATORY DIRECTOR'S OR PROVIDER/SUPPLIER REPRESENTATIVE'S SIGNATURE

TITLE

(X8) DATE

PRINTED: 05/30/2014 FORM APPROVED

	Division of Health Care Facilities FORM APPROVED										
STATEME		NT OF DEFICIENCIES OF CORRECTION	(X1) PROVIDER/SUPPLIER/CLIA	(X2) MULTIPLE CONSTRUCTION (X3) DA			TC DUBY				
		TOT BOTTLE TOW	IDENTIFICATION NUMBER:	A. BUILDING: 01 - MAIN BUIDING		(X3) DATE SURVEY COMPLETED					
			TN7400	B. WING							
NA	NAME OF PROVIDER OR SUPPLIER STREET AD				05/27/2014						
OTTLE ADDRESS, GIT, STATE, ZIP CODE											
GOOD SAMARITAN SOCIETY - FAIRFIELD GL/ CROSSVILLE, TN 38558											
	X4) ID REFIX	SUMMARY STATEMENT OF DEFICIENCIES ID PROVIDER'S PLAN OF CORRECTION									
	TAG	(EACH DEFICIENCY MUST BE PRECEDED BY FULL REGULATORY OR LSC IDENTIFYING INFORMATION)		PREFIX (EACH CORRECTIVE ACTION TAG CROSS-REFERENCED TO THE DEFICIENCY)		SHOULD BE COMPLETE					
	N 843	Continued From pa	ige 1	N 843							
	revealed, the use of a multi-plug adaptor and a										
	i	broke ground plug :	on the hair dryer. National Fire I								
		Frotection Associat	lon (NFPA) 99,8.4.12.5.		cont.						
	The findings were verified by the administrator				N 843 – Building Standards						
		and acknowledged the exit conference	by the administrator during in		5. Facility will be in compliance						
		are exit confetence	3/2//14.		by7/4/14.	7					
	N 848	1200-8-608 (18) B	uilding Standards	N 848	•		,				
		(18) It shall be dem-	onstrated through the				ļ				
		submission of plans	and specifications that in								
	each nursing home a negative air pressure shall be maintained in the soiled utility area, tollet			N 848 – Building Standards							
	room, janitor's closet, dishwashing and other			1. Applied fire seal to door 6/19	V1.4						
	such soiled spaces, and a positive air pressure shall be maintained in all clean areas including				and door is now air tight.	V14	.]				
		but not limited to, clean linen rooms and clean utility rooms.			2. All fire doors are at risk for the	hie					
		dimiy rooms.	1		deficient practice. All fire doors	in i					
					the skilled center were checked t	For					
	1	This Rule is not me	f as suidonand hur		proper closure on 5/27/14 and w	ere					
		Based on observation	Ons. it was determined the		found to be in working order and closed properly.	1					
		facility failed to main	itain negative air pressure.		property.	į					
		The findings include	_{id:}		All fire doors are checked						
		·			monthly by the maintenance	_	-				
		Observation of the k	titchen on 2/27/14 revealed,		department and recorded in TEL	ა.					
	the house keeping closet door will not close within the door frame.			4. Maintenance Department will							
		-			complete a safety audit on the fir	re l					
		The finding was veri	fied by the maintenance	-	doors monthly x3 and then quart	erly.					
		during the exit confe	riedged by the administrator erence on 5/27/14	}	Audits will be reported to the que committee for recommendations	ality					
					commutee for recommendations	•					
	ĺ		f		5. Facility will be in compliance	,					
				İ	7/4/14.						
ivisio	л of He	alth Care Facilities				i					